



APC NetShelter Metered Rack
PDU, 0U, 1PH, 7.4kW 230V 32A,
36 C13 and 6 C19 outlets, IEC 309
2P+E cord

AP8853

Overview

Presentation

APC Metered Rack Power Distribution Units (PDUs) provide active metering to enable energy optimization and circuit protection. The output and input connections are (36) C13 & (6) C19, and the cable length is 3m. User-defined alarm thresholds mitigate risk with real-time local and remote alerts to warn of potential circuit overloads. Metered Rack PDUs provide power utilization data to allow Data Center Managers to make informed decisions on load balancing and right sizing IT environments to lower the total cost of ownership. Metered Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and ultra-low profile circuit breakers. Users can access and configure Metered Rack PDUs through secure Web, SNMP, or Telnet Interfaces which are complimented by APC Centralized Management platforms using InfraStruxure Central, Operations, Capacity, and Energy Efficiency.

Lead Time

Usually in Stock

Main

Colour	Black
Product Or Component Type	PDU
Pdu Type	Metered
Cord Length	3.00 m
Number Of Cables	1
Provided Equipment	Installation guide Rack mounting brackets Serial configuration cable Safety guide

Complementary

Input Voltage	200 V 208 V 230 V
Height	179.1 cm
Width	5.6 cm
Output Voltage	230 V
Depth	4.4 cm
Net Weight	6.93 kg
Mounting Location	Side
Mounting Preference	No preference
Input Plug Type	IEC 60309 32 A
Mounting Mode	2P + E Rack-mounted
Rack Units	0U

Usb Compatible	No
Mounting Position	Vertical
Permissible Voltage	220...240 V
Max Line Current	32 A
Input Current Limits	32 A
Load Capacity	7400 VA
Network Frequency	50/60 Hz
Outlet Type And Quantity	36 IEC 60320 C13 6 IEC 60320 C19

Environment

Product Certifications Standards	VDE IEC 60950
Ambient Air Temperature For Operation	-5...60°C 5...95 %
Relative Humidity Operating Altitude	0...10000 ft -25...65 °C
Ambient Air Temperature For Storage	5...95 % 0.00...
Storage Relative Humidity Storage Altitude	15240.00 m

Packing Units

Unit Type Of Package	PCE 1
Number Of Units In Package	200 cm
Package Height Package	10.7 cm
Width Package Length	16.2 cm
Package Weight	8.56 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium](#)

[Guide to assess a product's sustainability](#)



Energy Efficient



Take-back



Transparency



RoHS/REACH

Resource performance

☒ Energy Efficient Product

☒ Take-Back Program Available

Well-being performance

☒ Lead Free

☒ Mercury Free

☒ Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant with Exemptions

Environmental Disclosure

[Product Environmental Profile](#)

Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile

[End of Life Information](#)