


## 5R2UM-S06



The OPT-X 1000i SDX Rack-Mount Enclosure allows for interconnect or cross-connect between backbone cable and active equipment while using minimum rack space in a frame or cabinet setting. The enclosure's features and design allow for easy field termination of connectors, splicing, or pre-terminated plug-n-play solutions. The fiber enclosure is primarily used in data centers, equipment rooms, and telecommunication rooms.



Color: Black

UPC Code: 078477516874

Country Of Origin: Please Contact

**Customer Service** 

## **Features and Benefits**

15-inch depth for high-density fiber termination and/or splicing

Stackable and adjustable fiber rings simplify cable organization

Front saddles pivot for improved patch cord routing Removable front and rear covers offer better access to the

Removable front and rear covers offer better access to the interior of the enclosure

Removable rubber grommet allows for pre-terminated fiber trunk install, protects cable, and minimizes dust build-up Sliding tray (an option in 1RU and 2RU enclosures) glides forward and backward for front and rear bulkhead access after installation, and removes completely from enclosure for ease of field terminations and splicing

Constructed of 16-gauge steel, powder-coated black 1RU or 2RU Retrofit Sliding Trays, sold separately, allow for higher-density applications using HDX MTP® Cassettes or HDX Adapter Plates (sliding tray does not accommodate splice trays)

Convert to HDX cassettes or adapter plate using conversion bracket (sold separately)

## Patents\*

## MX400781

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.



Phone: 01 424 2414 Email: sales@rwlas.com