

## PRODUCT SPECIFICATIONS

41084-xxx, 41085-xxx, 41086-xxx

# QUICKPORT™ Fiber Optic Adapters (ST, SC, LC, and MTP®)

## APPLICATION

QUICKPORT FiberOptic Adapters provide connectivity for workstation cabling termination on single-mode and multimode fiber cable. QUICKPORT bulkhead modules snap into any housing with the QUICKPORT name: flush-and surface-mount outlets, multimedia outlet system (with adapter), patch panels, and patch blocks.



QUICKPORT SC  
Shuttered Adapter



QUICKPORT  
SC/APC Adapter



QUICKPORT ST  
Adapter



QUICKPORT  
MTP Adapter



QUICKPORT LC  
Shuttered Adapter

## SPECIFICATION

QUICKPORT FiberOptic Adapters for fiber optic cabling media shall be individual snap-in style and shall fit into QUICKPORT panels. The LC, SC, and ST Adapters shall be compatible with single-mode, multimode, and laser-optimized multimode connectors, and available in zirconia ceramic or phosphor bronze sleeves. LC Shuttered Adapters shall be IP5x-rated, and shall open and close automatically with the insertion and removal of an LC connector.

## DESIGN CONSIDERATIONS

- QUICKPORT Adapters snap into QUICKPORT panels or modules
- ST and SC QUICKPORT Adapters are available in standard colors of ivory, white, gray, and black
- Internal patented shutters on LC adapters eliminate the need for dust plugs to reduce waste, speed deployment, and ensure safer installation
- Shuttered LC Adapter door will illuminate when a VFL is used for fiber traceability
- Shuttered LC Adapter is IP5x-rated for limited protection against dust ingress
- Use in permanent or temporary applications
- ST, SC, and LC QUICKPORT Adapters are available with zirconia ceramic or phosphor bronze sleeves, and are compatible with single-mode, multimode, and laser optimized (LC only)
- MTP Adapter key up to key down for single-mode applications
- SC Shuttered Adapter (41085-xxC) not compatible with 41089 series of Surface-Mount QUICKPORT Boxes

## STANDARDS & REGULATIONS

- ANSI/TIA-568.3-D
- ANSI/TIA-604-2 (ST), -38 (SC), -5 (MTP), -10B (LC)
- IEC 60529 IP5x

## MECHANICAL SPECIFICATIONS

Dimensions:	See page two
Materials:	
QuickPort Housing:	Snap-in module bodies are high-impact, fire-retardant plastic rated UL 94V-0
ST Fiber Adapter:	Single-mode: zirconia ceramic sleeve Multimode: phosphor bronze sleeve
SC Fiber Adapter:	Single-mode: zirconia ceramic sleeve Multimode: phosphor bronze sleeve
LC Fiber Adapter:	Single-mode: zirconia ceramic sleeve LOMM: zirconia ceramic sleeve Multimode: zirconia ceramic sleeve

## COUNTRY OF ORIGIN


41084 (ST) and 41085 (SC): Taiwan  
41085 (SC Shuttered and MTP): USA  
41086 (LC Shuttered): USA

## WARRANTY INFORMATION

For Leviton product warranties, go to [Leviton.com/NS/Warranty](http://Leviton.com/NS/Warranty)

41084-xxx, 41085-xxx, 41086-xxx

**PRODUCT SPECIFICATIONS**  
**41084-xxx, 41085-xxx, 41086-xxx**



**PART NUMBERS**

**Description**

**Part No.**

QUICKPORT Duplex LC shuttered, MM, zirconia ceramic sleeve, beige	41086-ML*
QUICKPORT Duplex LC shuttered, 10G LOMM, zirconia ceramic sleeve, aqua	41086-LL*
QUICKPORT Duplex LC shuttered, SM, zirconia ceramic sleeve, blue	41086-SL*
QUICKPORT Simplex SC shuttered, MM, phosphor bronze sleeve, female front/back	41085-M'C
QUICKPORT Simplex SC shuttered, SM, zirconia ceramic sleeve, female front/back	41085-S'C
QUICKPORT Simplex SC/APC, SM, zirconia ceramic sleeve, female front/back	41085-AS^
QUICKPORT ST, MM, phosphor bronze sleeve	41084-S'F
QUICKPORT ST, SM, zirconia ceramic sleeve	41084-S'Z
QUICKPORT MTP®, SM/MM, key up to key down (opposed)	41085-TP†
QUICKPORT MTP, MM, key up to key up (aligned)	41085-TB†

\* = Colors: Ivory (I), White (W), Gray (G), Black (E), Yellow (Y), Red (R), Blue (L), Green (V), Orange (O)

^ = Colors: Ivory (I), White (W), Gray (G), Black (E)

† = Colors: White (W), Black (E)

^ Minimum order quantity and lead times may apply.

